

Codice Dianflex: 351-F5020

# FLESSIBILI ANTIVIBRANTI ANTI-VIBRATION FLEXIBLES

IN ACCIAIO ZINCATO  
IN GALVANIZED STEEL








## DATI TECNICI - TECHNICAL DATA:



Flessibili antivibranti made in Italy rivestiti con treccia in Acciaio Zincato ed interno in tubo in gomma alimentare EPDM utilizzati per il collegamento tra la rete idrica e pompe, caldaie, autoclavi e depuratori, sono disponibili nelle misure da 1/2" fino a 2". Tutti i flessibili sono raccordati con macchine automatiche ed il risultato è l'assoluta precisione di ogni pezzo prodotto per una garanzia di totale qualità.

*Made in Italy anti-vibration flexible hoses, galvanized steel braided, with internal in non-toxic EPDM rubber, used for the connection between the water mains and pumps, boilers, autoclaves and water conditioner; available from 1/2" to 2" size. All the hoses are connected with automatic machines and the result is the absolute precision of each produced piece for a total quality guarantee.*

## CARATTERISTICHE - FEATURES:

	PRESSIONE D'ESERCIZIO WORKING PRESSURE 	PORTATA A 3 BAR FLOW RATE AT 3 BAR 	TEMPERATURA D'IMPIEGO WORKING TEMPERATURE 	FORO MINIMO PASSAGGIO D'ACQUA FITTING INNER DIAMETER 	RAGGIO CURVATURA MINIMO MINIMUM BENDING RADIUS 
Tubo Dn13 - 1/2"	10 BAR	120 lit/min	-10°C - +90°C	9,3 mm	45 mm
Tubo Dn19 - 3/4"	10 BAR	120 lit/min	-10°C - +90°C	15 mm	70 mm
Tubo Dn25 - 1"	10 BAR	200 lit/min	-10°C - +90°C	20 mm	100 mm
Tubo Dn32 - 1 1/4"	6 BAR	400 lit/min	-10°C - +90°C	26 mm	190 mm
Tubo Dn40 - 1 1/2"	6 BAR	700 lit/min	-10°C - +90°C	32 mm	230 mm
Tubo Dn50 - 2"	4 BAR	1.050 lit/min	-10°C - +90°C	41 mm	300 mm

## MATERIALI - MATERIALS

TUBO HOSE		Ø INTERNO INNER Ø	Ø ESTERNO OUTER Ø	Treccia Ø 0,30mm in Acciaio Zincato Tubo interno: gomma EPDM atossico. <i>wires braid Ø 0,30mm in steel galvanized</i> <i>Internal pipe: EPDM rubber, atoxic.</i>
	Tubo Dn13 - 1/2"	13 mm	19 mm	
	Tubo Dn19 - 3/4"	19 mm	27 mm	
	Tubo Dn25 - 1"	25 mm	33 mm	
	Tubo Dn32 - 1 1/4"	30 mm	42 mm	
	Tubo Dn40 - 1 1/2"	40 mm	52 mm	
	Tubo Dn50 - 2"	50 mm	62 mm	
RACCORDI FITTINGS		CW614N CW617N		Ottone CW614N e CW617N giallo o nichelato Brass CW614N and CW617N yellow or nickel plated
BUSSOLE SLEEVES		Alluminio 99,5% Aluminium 99,5%		