

UNITA' INTERNA / INDOOR UNIT
TERMINALE A CONSOLE
 CONSOLE TYPE



IONIZZATORE
 AL PLASMA
 PLASMA IONIZER

413-D32UIC-09

413-D32UIC-12

413-D32UIC-18



LA CONSOLE E' COMBINABILE SOLO CON LE UNITA' ESTERNE MULTISPLIT

dati tecnici

codice		413-D32UIC-09	413-D32UIC-12	413-D32UIC-18
CAPACITA' / CAPACITY				
Raffreddamento/ Cooling	kW	2,70	3,50	5,20
Riscaldamento/ Heating	kW	2,80	3,75	5,33
Deumidificazione/ Dehumidification	L/h	0,80	1,20	3,80
ALIMENTAZIONE / POWER SOURCE	V/ ph / Hz	220-240/1/50		
UNITA' INTERNA/ INDOOR UNIT				
Volume d'aria/Air flow	m3/h	500/430/410/ 370/330/280/250	600/520/480/ 440/400/360/280	700/650/580/520/46 0/410/320
Pressione sonora/Sound pressure	dB (A)	40/36/34/32/30/26 /23	42/40/38/36/34/31/25	47/45/42/40/37/35/ 31
Potenza sonora/Sound power	dB (A)	52/48/46/44/42/38 /34	52/50/48/46/44/41/35	57/55/52/50/47/45/ 41
Dimensioni (LxAxP)/Dimensions (WxHxD)	mm	700x600x215		
Peso (netto/lordo) / Weight (net/gross)	kg	15,5/18,5		
REFRIGERANTE E LINEE FRIGORIFERE/ REFRIGERANT AND PIPING				
Dimensioni Liquido-Gas/ Piping size liquid-gas	mm (inch)	Ø6 (1/4") - Ø9,52 (3/8")		Ø6 (1/4") - Ø12,7 (1/2")



START UP
 A BASSO SPUNTO
 LOW VOLTAGE
 RANGE



BLOCCO
 BAMBINO
 CHILD BLOCK



FUNZIONE
 TURBO
 TURBO BUTTON



FUNZIONE
 A LED
 LED DISPLAY



TIMER 24H
 TIMER 24H



DEUMIDIFICAZIONE
 DEHUMIDIFYING



AUTO DIAGNOSI
 SELF DIAGNOSIS



SBRINAMENTO
 INTELLIGENTE
 INTELLIGENT
 DEFROSTING



MEMORIA
 RIPRISTINO AUTOM
 AUTO RESTART
 MEMORY