

Termoarredi

Kalura Curvo

Kalura



TERMOARREDO KALURA CURVO

ATON

Materiale Acciaio
Finiture Cromo
Dimensioni H 800 / 1200 / 1500 / 1800 mm

Specifiche Spessore profili 1,2 mm, elementi orizzontali a tubi tondi diam. 22 mm spessore 0.90 mm, pressione massima di esercizio 8 bar. Fornitura standard: 3/4 fissaggi, 1 valvola sfiato 1/2



CURVO H 800 MM

| | | |
|----------------|------------------|------------------------------|
| 432-HKC080-C40 | Int. 400 - L 450 | $\Delta T 50^{\circ}C$ 215 W |
| 432-HKC080-C45 | Int. 450 - L 500 | $\Delta T 50^{\circ}C$ 236 W |
| 432-HKC080-C50 | Int. 500 - L 550 | $\Delta T 50^{\circ}C$ 258 W |
| 432-HKC080-C55 | Int. 550 - L 600 | $\Delta T 50^{\circ}C$ 280 W |



CURVO H 1120 MM

| | | |
|----------------|------------------|------------------------------|
| 432-HKC120-C40 | Int. 400 - L 450 | $\Delta T 50^{\circ}C$ 301 W |
| 432-HKC120-C45 | Int. 450 - L 500 | $\Delta T 50^{\circ}C$ 330 W |
| 432-HKC120-C50 | Int. 500 - L 550 | $\Delta T 50^{\circ}C$ 360 W |
| 432-HKC120-C55 | Int. 550 - L 600 | $\Delta T 50^{\circ}C$ 391 W |



CURVO H 1500 MM

| | | |
|----------------|------------------|------------------------------|
| 432-HKC150-C40 | Int. 400 - L 450 | $\Delta T 50^{\circ}C$ 404 W |
| 432-HKC150-C45 | Int. 450 - L 500 | $\Delta T 50^{\circ}C$ 443 W |
| 432-HKC150-C50 | Int. 500 - L 550 | $\Delta T 50^{\circ}C$ 483 W |
| 432-HKC150-C55 | Int. 550 - L 600 | $\Delta T 50^{\circ}C$ 525 W |



CURVO H 1760 MM

| | | |
|----------------|------------------|------------------------------|
| 432-HKC180-C40 | Int. 400 - L 450 | $\Delta T 50^{\circ}C$ 481 W |
| 432-HKC180-C45 | Int. 450 - L 500 | $\Delta T 50^{\circ}C$ 528 W |
| 432-HKC180-C50 | Int. 500 - L 550 | $\Delta T 50^{\circ}C$ 580 W |
| 432-HKC180-C55 | Int. 550 - L 600 | $\Delta T 50^{\circ}C$ 631 W |



Kalura

